

CLAIMS

WHAT IS CLAIMED IS:

- 1 1. A hybrid microlens, comprising two layers that are transparent at the wavelength of
2 interest:
3 a first layer with a low index of refraction;
4 a second layer bonded to said first layer; and
5 said second layer having an optical focusing element formed on the non-
6 adjacent surface, said second layer being substantially thinner and having a higher
7 index of refraction than the first layer, whereby both the microlens sag and the sum of
8 the two layer thicknesses are minimized.
- 9 2. The hybrid microlens of claim 1 wherein said optical focusing element is a refractive
10 microlens.
- 11 3. The hybrid microlens of claim 1 wherein said optical focusing element is formed by dry
12 etching.
- 13 4. The hybrid microlens of claim 1 wherein said first layer comprises fused silica or optical
14 glass.
- 15 5. The hybrid microlens of claim 1 wherein said second layer is a semiconductor.
- 16 6. The hybrid microlens of claim 1 wherein said second layer is comprised substantially of
17 silicon.
- 18 7. The hybrid microlens of claim 1 wherein an antireflection layer is applied at the interface
19 between the first and second layers, and said antireflection layer is optimized for the
20 refractive indices of the two adjacent layers.
- 21 8. The hybrid microlens of claim 1 wherein said second layer is divided into a plurality of

Sub
A3
could

~~portions for reduced mechanical stress in the layer.~~

- 23 9 The hybrid microlens of claim 1 wherein said bonding process is via epoxy.
- 24 10. The hybrid microlens of claim 1 wherein said bonding process is via anodic bonding.
- 25 11. An optical construction which substantially reduces return signal from an optical fiber,
26 which is perpendicular to and butt-coupled to a planar optical surface, comprising:
27 A small non-perpendicular surface formed on said planar optical surface in the
28 vicinity of the core of said optical fiber, whereby optical reflection from said non-
29 perpendicular surface is directed away from said optical fiber.
- 30 12. The optical construction of claim 11 and further comprising an optical epoxy that fills the
31 gap between the optical fiber end face and the adjacent non-perpendicular surface, said
32 optical epoxy having an index that approximately matches that of the optical fiber to
33 reduce optical loss and minimize polarization sensitivity.
- 34 13. The optical construction of claim 11 wherein said non-perpendicular surface is
35 approximately a planar surface.
- 36 14. The optical construction of claim 11 wherein said non-perpendicular surface is formed by
37 dry etching.
- 38 15. The optical construction of claim 11 wherein said optical fiber end face is not
39 perpendicular to the fiber longitudinal axis.

- 40 16. A method for making a plurality of hybrid microlenses, comprising the steps of:
41 Anti-reflection coating a second layer;
42 Bonding the second layer to a first layer which has a lower index of refraction
43 than the second layer;
44 Thinning and polishing the second layer;
45 Forming a plurality of optical focusing elements on the non-adjacent surface of

46

the second layer.

17. The method of claim 16 wherein said optical focusing element is a refractive microlens.

48

18. The method of claim 16 wherein said optical focusing element is formed by dry etching.

49

19. A method for substantially reducing optical return signal from an optical fiber, which is perpendicular to, and butt-coupled to a planar optical surface, comprising the steps of:

50

51

forming non-perpendicular local surfaces on said planar optical surface in the

52

vicinity of the core of said optical fiber;

53

angle cleaving or angle polishing said optical fiber end face;

54

filling the gap between said optical fiber and said non-perpendicular local

55

surface with an optical epoxy having an index of refraction that approximately

56

matches that of said optical fiber.

57

20. The method of claim 17 wherein the step of forming non-perpendicular local surfaces is

58

by dry etching.

002660-651E2960

ADD
AS 7